



The obvious choice



GenesisBlower

The obvious choice for whirlpools and spas

- Modern design
- Unique performance
- Complete with massage mode "pulsating effect"
- Whisper quiet
- Variable speed control option




BALBOA
water group

GenesisBlower

A unique combination of standard of standard and sophisticated features. The Genesis Blower is developed with a focus on design and function with continuous improvement. Enhanced with an excellent performance level, whisper quiet, multiple features and reliability. The extensive Genesis range enables you to find the ideal blower for your needs. Complete with power Options 500, 700, 900 & 1200W, and voltage Options 230V, 50Hz. 120V, 60Hz* (*only available in 500W).

Measurements apply to all models.



FeaturesOptions

FEATURES	
NN	Standard blower for electronic control/touch pad
AN	Pneumatic air switch. Pneumatic on/off blower
HN	Heater. Standard blower for electronic control/touch pad with built-in heating element to reduce cold air in upstart.
AH	Pneumatic air switch & heater. Pneumatic on/off blower with built-in heating to reduce cold air in upstart.
VN*	Variable speed. Standard blower including variable massage mode and automatic dry-out when using special touch pad. UK01658A connected directly to blower. No separate control panel needed. See functional description under "VH."
VH*	Variable speed & heater. Standard blower including variable massage mode and automatic dry-out when using special touch pad. UK01658A connected directly to blower. No separate control panel needed. The blower has built-in heating element to reduce cold air in upstart. Functional description for preset programme: <ul style="list-style-type: none"> • Press the on/off button = high speed. • Press the +/- button = in-/decrease blower speed. • Press the ~ button = massage mode "pulsating effect" Automatic stop: blower stops 30 min. After the user has operated one of the buttons for the last time. Drying cycle: 30 min. After manual or auto switch off, the blower starts up at high speed for 2 seconds. It then drops to low speed and increases gradually to high speed within 30 sec. The blower will then continue running 4½ minutes at high speed to drain remaining water from the pipes.
ANT*	Pneumatic air switch & 3-speed. Pneumatic on/off blower including massage mode, automatic dry-out when using standard pneumatic air switch. See functional description under "AHT."
AHT*	Pneumatic air switch, 3-speed & heater. Pneumatic on/off blower including massage mode, automatic dry-out when using standard pneumatic air switch. With built-in heating element to reduce cold air in upstart. Functional description for preset programme: <ol style="list-style-type: none"> 1. Press the pneumatic button = high speed. 2. Press the pneumatic button = medium speed. 3. Press the pneumatic button = low speed. 4. Press the pneumatic button = massage mode "pulsating effect". 5. Press the pneumatic button = off. Automatic stop: blower stops 30 min. after the user has operated one of the buttons for the last time. Drying cycle: 30 min. after manual or auto switch off, the blower starts up at high speed for 2 seconds. It then drops to low speed and increases gradually to high speed within 30 sec. The blower will then continue running 4½ minutes at high speed to drain remaining water from the pipes.
* The preset programme can be changed via jumpers inside the blower to change order of functions or to eliminate the drying cycle. Request manual for detailed information.	

FeaturesOptions (continued)

POWER OPTION	
50	500W
70	700W
90	900W
120	1200W
VOLTAGE OPTIONS	
1	120V, 60HZ
2	230V, 50HZ
PACKING OPTION	
S	Single Packed
B	Bulk Packed
SPECIAL APPROVALS	
UL	UL Recognized

ModelOverview

500W				
PART NUMBER	MOTOR W	HEATER W	TOTAL W	PNEU.
GB50-2AN-S	500	–	500	X
GB50-2AH-S	500	250	750	X
GB50-2ANT-S	500	–	500	X
GB50-2AHT-S	500	250	750	X
GB50-2HN-S	500	250	750	–
GB50-2NN-S	500	–	500	–
GB50-2VN-S	500	–	500	–
GB50-2VH-S	500	250	750	–

900 & 1200W				
PART NUMBER	MOTOR W	HEATER W	TOTAL W	PNEU.
GB90-2AN-S	900	–	900	X
GB90-2ANT-S	900	–	900	X
GB90-2HN-S	900	250	1150	–
GB90-2NN-S	900	–	900	–
GB120-2HN-S	900	–	900	–
GB120-2NN-S	1200	–	1200	–
GB120-2AN-S	1200	–	1200	–

700W				
PART NUMBER	MOTOR W	HEATER W	TOTAL W	PNEU.
GB70-2AN-S	700	–	700	X
GB70-2AH-S	700	250	950	X
GB70-2ANT-S	700	–	700	X
GB70-2AHT-S	700	250	950	X
GB70-2HN-S	700	250	950	–
GB70-2NN-S	700	–	700	–
GB70-2VH-S	700	250	950	–

Note: All standard models can run with variable speed when connected to a control panel. The Genesis range of Class I blowers is manufactured in accordance with European norms and specific 120V models are UL Recognized. All part numbers in the model overview indicate single packed versions. Bulk packed versions are also available (64 pcs. per pallet).

